

WWA WATERWISE A/C® AIR CONDITIONING WATER HEATING SYSTEMS

- Indoor or outdoor packaged units
- For use in commercial and industrial applications (manufacturing plants, laundry rooms, kitchens)
- Fail safe operation with controls designed to supply air conditioning and hot water when you need it
- Field adjustable airflow configurations

OPERATING RANGE

- Entering Water
40°F thru 120°F
- Entering Air
55°F thru 95°F
- External Static Pressure
.5" thru 1.0"

OPTIONS AVAILABLE

- Outdoor condenser for year-round air-conditioning
- Hot gas partial reheat for superior dehumidification
- Variety of auxiliary heating coils
- Stainless steel cabinet
- CFC-free R-407C refrigerant
- Cupronickel coaxial condenser



QUALITY FEATURES

- Vented copper double shell hot water heat exchanger
- Meets the requirements for potable water
- Satin-coated steel casing with powder paint finish
- Built-in water heating controls and circulating pump(s)
- HyPoxy® coated fin coils
- Heavy duty enclosure
- Adjustable motor pulley
- User friendly
- Voltages available:
208-230, 460, 575/3/60



Model	Total	Cooling Sensible		Heating			Nominal	Dimensions (in.)				Net Weight	
		Btu/h	EER ¹	Btu/h	COP ¹	usgpm		cfm	Out/cond.	Condenser	Combined		
WWA	Btu/h	Btu/h	EER ¹	Btu/h	COP ¹	usgpm	cfm	W	H	D	H	lb	lb
042	41,651	29,304	16.10	49,337	5.59	12	1040	42	25	42	18	150	680
066	66,360	46,128	16.43	78,555	5.70	19	1600	56	25	42	18	220	880
088	87,492	61,610	15.72	104,460	5.50	25	2160	60	30	48	20	260	1040
116	115,606	81,739	15.52	138,301	5.44	38	2880	78	30	54	20	350	1350

1. At 80°F entering water and 89°F leaving water temperature

Note: The information in this catalogue is accurate at the time of printing. However, in keeping with company policy to continuously improve our products and maintain our technological edge, we reserve the right to change designs and specifications without notice.