

PSC PORTABLE SPOT COOLERS

- Indoor packaged portable units, provide instant spot cooling precisely where it is required. Simply roll it in.
- Provides cool air for specific areas in computer rooms, rentals, equipment protection, construction, warehousing, aircraft service, offices

QUALITY FEATURES

- Condensate storage tank with automatic unit shut-off when full (models 009 to 024)
- Condensate pump kit (models 036 to 060)
- Switch selectable, ventilation or cooling mode
- Heavy duty rubber wheels
- 8 ft electrical cord
- Satin-coated steel casing with powder paint finish
- Thermally protected motors
- Refrigerant high and low pressure cut-out switches
- Thermostatic expansion valve
- Low ambient switch prevents compressor operation at low ambient temperatures
- Compressor short cycle protection
- Panel mounted sight glass
- Supply flexible duct included (24" long)
- Voltages available:
115, 208-230/1/60

OPERATING RANGE

- Entering Air
60°F thru 100°F
- Relative Humidity
40% thru 70%

OPTIONS AVAILABLE

- Water-cooled condenser
- Condensate pump kit (models 009 to 024)
- Ducted condenser exhaust
- 3 phase units (models 036 to 060)



Model	Cooling ¹	Evap	Cond.	Unit amps (60 Hz)		Max. ESP in. wg	Dimensions (in.)			Net Weight lb
	Btu/h	cfm	cfm	115/1	208-230/1		L	H ²	P	
009	9,500	250	600	9.2	4.6	0.2	20	40	30.5	190
012	11,900	350	800	10.6	5.3	0.2	20	40	30.5	200
014	13,500	450	900	13.2	7.4	0.2	20	40	30.5	220
018	18,100	525	1200	20.3	9.4	0.2	20	40	30.5	250
024	22,100	700	1400	n/a	11.8	0.2	23	40	35	275
036	36,900	1050	3400	n/a	17.2	1.0	29	38	50	350
048	48,000	1400	3300	n/a	21.8	1.0	29	38	50	400
060	60,000	1750	3200	n/a	28.3	1.0	29	38	50	450

1. At 90°F DB, 78°F WB

2. Add 5" for wheels